

TECHNICAL INFORMATION SHEET

5S SPEED FLOOR STRIPPER

Product Description

Universal stripper for removing polish and maintenance films from water resistant hard floors.

Features and Benefits

- Effectively penetrates and removes maintenance and polish layers.
- Versatile thanks to a well-balanced ratio of alkali and solvent ingredients.
- Low foaming for speed of use and ultimate wet vacuuming.
- Optimum combination of efficiency and economy.
- Can be applied on all water-resistant floors.
- Effective in all water conditions.

Use Instructions

Mop stripping

- 1. Dilute 200 ml of Speed Floor Stripper per litre of hot or cold water (1:5 dilution).
- 2. Mop the floor liberally.
- 3. Leave for 5 to 10 minutes.
- 4. Remove the slurry with a mop or wet vac.

Scrubbing machine

- 1. Dilute 200 ml of Speed Floor Stripper per litre of hot or cold water (1:5 dilution).
- 2. Mop the floor liberally.
- 3. Leave for 5 to 10 minutes and then scrub with a slow machine fitted with a black pad.
- 4. Remove the slurry with a mop or wet vac.

Spray stripping

- 1. Dilute 100 ml of Speed Floor Stripper per litre of hot or cold water (1:10 dilution).
- 2. Spray a small area and immediately scrub with a machine fitted with a black pad.
- 3. Remove any residue with a damp mop and allow the floor to dry.

Safe Handling and Storage

See visual information to right.

Full guidance on the handling and safe use of the product can be obtained from the Safety Data Sheet.

Store in original container.

Avoid extremes of temperature.



Health & Safety

HAZARD AS SUPPLIED



Causes severe skin burns and eye damage.





HAZARD WHEN USED AT RECOMMENDED DILUTION.



Not classified. Wear gloves for prolonged use.



Page 1 of 2

For reorder contact: B I O Detergents & Disinfectants Trading L.L.C.

PO Box 251116, Dubai, U.A.E Tel: 04 2666 572

Web: www.biodubai.com Email: info@biodubai.com

Manufactured by Ionic Products Ltd, Unit 26, Blaris Ind. Est., Altona Rd. Lisburn, Co. Antrim, N. Ireland, BT27 5QB

Technical Information

Appearance: Blue liquid

pH: >11.5

Relative density: 1.101 Odour: Characteristic

Solubility: Fully miscible in water

The above data is typical of normal production and should not be taken as a specification.

Materials Compatibility

Do not use on unsealed wood, painted surfaces or linoleum floors.

Problem Solving

Problem	Possible Cause	Solution
Poor polish film removal	Incorrect dilution	Increase dilution
	Insufficient dwell time	Allow at least 5 minutes contact time before scrubbing
	Heavy polish build-up	Repeat stripping process and/or use a stronger dilution of stripper solution
	Incorrect/worn pad	Change pad for correct/new one

Available Pack Sizes

SKU Pack Size BD5S/C 2x5L

Version 1 | Issue Date: 27/05/2020 | Page 2 of 2

Manufactured by Ionic Products Ltd, Unit 26, Blaris Ind. Est., Altona Rd. Lisburn, Co. Antrim, N. Ireland, BT27 5QB

Web: www.biodubai.com Email: info@biodubai.com